

MULTI-SERVICE DOT/ASME 420 LB. CONTAINER VAPOR VALVES



APPLICATION:

Intended for use in vapor withdrawal service for DOT or ASME containers ranging from 420 lbs to 100 gallons LPG capacity as fuel line shutoff valves in combination with a fill and vapor relief valve. Ideal for on-site filling without interruption of service by combining all functions into a single 1" tank opening.

FEATURES:

- One piece forged brass body construction.
- Integral fill valve.
- Easy to repair or replace bonnet assembly.
- Integral 375 DOT or 250 ASME psi relief valve, specify DOT or ASME upon order.
- Heavy duty replaceable zinc hand wheel.
- 1/8" FNPT plugged test port
- Liquid splash tube to prevent liquid in vapor opening.
- Female POL vapor outlet with shutoff.

PART NUMBER	DESCRIPTION	DIPTUBE LENGTH	RELIEF STD PSI
LP-MES-PVE2035AT-11.7	Multi-Service 420 lb. DOT Cluster Valve 1" MNPT with Diptube	11.7"	375
ACCESSORIES			
LP-MES-3250-8LH-KIT	Replacement Bonnet Kit		
LP-MES-1901S	Replacement Handle		
LP-MES-2035-100-KIT	Fill Valve Repair Kit		

THE PRODUCTS, KNOWLEDGE AND EXPERIENCE
TO SERVE YOUR NEEDS



Billings, MT | Valley City, ND | Yakima, WA

Phone: 800-437-9702 | Fax: 800-313-3299 | www.feinc.com

February 2016